



FAT File System Test Suite User Guide

Version 1.50

For use with FAT File System Test Suite version 2.17 -
2.23

Table of Contents

| | |
|------------------------------------|----|
| 1. System Overview | 3 |
| 1.1. Introduction | 4 |
| 1.2. Feature Check | 5 |
| 1.3. Packages and Documents | 6 |
| 1.4. Change History | 7 |
| 2. Source File List | 8 |
| 3. Configuration Options | 9 |
| 4. Running Tests | 10 |
| 4.1. f_dotest Function | 10 |
| 4.2. Setting up Your Drive | 11 |
| 4.3. Starting the Test | 12 |
| 5. Integration | 13 |
| 6. Version | 14 |

1. System Overview

This chapter contains the fundamental information for this module.

The component sections are as follows:

- [Introduction](#) - describes the main elements of the module.
- [Feature Check](#) - summarizes the main features of the module as bullet points.
- [Packages and Documents](#) - the *Packages* section lists the packages that you need in order to use this module. The *Documents* section lists the relevant user guides.
- [Change History](#) - lists the earlier versions of this manual, giving the software version that each manual describes.

All rights reserved. This document and the associated software are the sole property of HCC Embedded. Reproduction or duplication by any means of any portion of this document without the prior written consent of HCC Embedded is expressly forbidden.

HCC Embedded reserves the right to make changes to this document and to the related software at any time and without notice. The information in this document has been carefully checked for its accuracy; however, HCC Embedded makes no warranty relating to the correctness of this document.

1.1. Introduction

This guide is for those who want to test an HCC Embedded FAT file system.

This test suite allows you to test many file system functions, including the following:

- File creation and writing.
- Checking file content.
- Handling of "a", "a+", "w", and "w+" files.
- Concurrent access with "r" files.
- Formatting.
- Power failure.
- Finding and seeking.
- Renaming.
- Bad block detection.
- Partitions.
- Finding and deletion of Shift JIS Japanese character set files.
- File and directory operations with Shift JIS characters.

1.2. Feature Check

The main features of the module are the following:

- Provides a full test capability for HCC Embedded FAT file systems.
- Conforms to the HCC Advanced Embedded Framework.
- Designed for integration with both RTOS and non-RTOS based systems.
- Conforms to the HCC Coding Standard.

1.3. Packages and Documents

Packages

The table below lists the packages that you need in order to use this module.

| Package | Description |
|--------------------------------|--|
| <code>hcc_base_docs</code> | This contains the two guides that will help you get started. |
| <code>fs_fat_test</code> | The FAT file system test package. |
| <code>media_drv_base</code> | The Media Driver base package that provides the base for all media drivers that attach to the file system. |
| <code>psp_template_base</code> | The Platform Support Package (PSP) base package. |
| <code>oal_base</code> | The OS Abstraction Layer (OAL) base package. |

Documents

For an overview of HCC file systems and guidance on choosing a file system, see [Product Information](#) on the main HCC website.

Readers should note the points in the [HCC Documentation Guidelines](#) on the HCC documentation website.

HCC Firmware Quick Start Guide

This document describes how to install packages provided by HCC in the target development environment. Also follow the *Quick Start Guide* when HCC provides package updates.

HCC Source Tree Guide

This document describes the HCC source tree. It gives an overview of the system to make clear the logic behind its organization.

HCC FAT File System Test Suite User Guide

This is this document.

1.4. Change History

This section describes past changes to this manual.

- To download this manual or a PDF describing an [earlier software version, see File System PDFs](#).
- For the history of changes made to the package code itself, see [History: fs_fat_test](#).

The current version of this manual is 1.60. The full list of versions is as follows:

| Manual version | Date | Software version | Reason for change |
|----------------|------------|------------------|---|
| 1.50 | 2019-11-08 | 2.22 | Added TEST_PARTITIONS configuration option. |
| 1.40 | 2018-07-18 | 2.16 | Added psp_snprintf() to <i>PSP Porting</i> . |
| 1.30 | 2017-10-12 | 2.12 | Updated <i>Packages</i> list. |
| 1.20 | 2017-06-23 | 2.08 | New <i>Change History</i> format. |
| 1.10 | 2016-03-21 | 2.06 | Added <i>Change History</i> . |
| 1.00 | 2015-03-10 | 2.01 | First online version. |

2. Source File List

This section describes all the source code files included in the system. These files follow the HCC Embedded standard source tree system, described in the [HCC Source Tree Guide](#). All references to file pathnames refer to locations within this standard source tree, not within the package you initially receive.

Note: Do not modify any files except the configuration file and PSP files.

API Header File

The file `src/api/api_fat_test.h` should be included by any application using the system. This is the only file that should be included by an application using this module. It defines the [f_dotest\(\) function](#).

Configuration File

The file `src/config/config_fat_test.h` contains all the configurable parameters of the system. Configure these as required. This is the only file in the module that you should modify. For details of these options, see [Configuration Options](#).

Source Code File

The file `src/fat/test/fat_test.c` contains the source code. **This file should only be modified by HCC.**

PSP Files

These files in the directory `src/psp/target/fat_test` provide functions and elements that the core code needs to use, depending on the hardware. Modify these files as required for your hardware; see [Setting up Your Drive](#).

| File | Description |
|-----------------------------|--------------|
| <code>fat_testport.c</code> | Source code. |
| <code>fat_testport.h</code> | Header file. |

Version File

The file `src/version/ver_fat_test.h` contains the version number of this module. This version number is checked by all modules that use this module to ensure system consistency over upgrades.

3. Configuration Options

Set the system configuration options in the file **src/config/config_fat_test.h**. This section lists the available configuration options and their default values.

Note: The first two options only apply if USE_MALLOC is set.

FN_MAXVOLUME

The number of volumes. This is only needed for library builds. The default value is 3.

TEST_MALLOC_MAXFILES

Set this to 1 if you want to check the maximum number of files. The default value is 0.

TEST_PARTITIONS

Keep the default value of 1 to enable the partition handling test. Otherwise set it to 0.

TEST_FAT_MEDIA

The default value is F_FAT32_MEDIA.

MAX_BUFFER_SIZE

The size of the buffer used for test functions. A smaller buffer size results in fewer tests. Valid values are: 256, 512, 1024, 2048, 8192, 16384 and 32768. The default value is 32768.

- For the *f_writing* test set at least 2560.
- For the *f_seekpos* test set at least 8192 bytes. Lower values will result in fewer *f_seeking* tests.

RIT_NUM_OF_RECORDS

The number of RIT tests. The default value is 100.

TEST_OPEN_NONSAFE

Set this if non-safe open needs to be tested. (This is only valid if safe mode is allowed). The default value is 0.

4. Running Tests

This section shows how to run a test.

4.1. f_dotest Function

Use this function to run tests on a volume.

Format

```
void f_dotest ( uint32_t vol_id )&nbsp;
```

Arguments

| Argument | Description | Type |
|----------|-------------------------------|----------|
| vol_id | The ID of the volume to test. | uint32_t |

Return Values

None.

4.2. Setting up Your Drive

Editing fat_testport.c

To set up your drive for testing, modify the two lines in the PSP template file **fat_testport.c** described below.

- Line 41 initially appears as shown below. Edit this line to include the API file for the drive you want to test.

```
#include "../../api/api_mdriver_ram.h"
```

- Line 67 initially appears as shown below. Edit this line to change *ram_initfunc* to the **init()** function of the drive that you want to test. This should be exposed in the API file included at line 41.

```
ret = f_initvolume( (int)vol_id, ram_initfunc, vol_id );
```

This table shows examples of the **init()** functions used for the main drive types:

| Drive type | Function |
|---------------------|-----------------------|
| RAM | ram_initfunc() |
| Compact Flash (CFC) | cfc_initfunc() |
| MMC | mmc_initfunc() |
| Mass Storage | mst_initfunc() |

These can be seen in the **f_initvolume()** function.

Selecting Functions to Print Test Results

The **f_dump()** and **f_result()** functions in **fat_testport.c** call **printf()** to output the test results. You can replace these **printf()** calls with calls to appropriate functions that output to your required location.

4.3. Starting the Test

Use the function **f_dotest()** to run the tests on the specified volume. The following example code shows how to do this:

```
{  
    fs_init();      /* Initialize the file system */  
    fs_start();    /* Start the file system */  
    f_enterFS();   /* Register the task with the file system */  
    f_dotest( 0 ); /* Execute the test suite on the first volume */  
  
    .....  
}
```

5. Integration

The test suite is designed to be as open and as portable as possible. No assumptions are made about the functionality, the behavior, or even the existence, of the underlying operating system. For the system to work at its best, perform the porting outlined below. This is a straightforward task for an experienced engineer.

PSP Porting

The Platform Support Package (PSP) is designed to hold all platform-specific functionality, either because it relies on specific features of a target system, or because this provides the most efficient or flexible solution for the developer.

The test suite makes use of the following standard PSP functions:

| Function | Package | Element | Description |
|-----------------------|----------|------------|---|
| psp_getrand() | psp_base | psp_rand | Gets a random number. |
| psp_memset() | psp_base | psp_string | Sets the specified area of memory to the defined value. |
| psp_snprintf() | psp_base | psp_stdio | Sends formatted output to compose a string holding the same text that would be printed if <i>format</i> was used on psp_printf() . Instead of being printed, the content is stored as a <i>C string</i> in a buffer. |
| psp_sprintf() | psp_base | psp_stdio | Prints a string. |
| psp_strnlen() | psp_base | psp_string | Gets the length of a string. |
| psp_strncmp() | psp_base | psp_string | Compares two strings of defined length. |

6. Version

Version 1.50

For use with FAT File System Test Suite version 2.17 - 2.23